



Norwich Series Pendant



Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	
NW1222L	ALI	3-100W A21 (300W)	1-300W R40 (300W)	2	PC	AD AG	ST CH SM SP	CR SQ	
<ul style="list-style-type: none"> • W 12" • HT 27" • OAH 6' (OverAll Height) 									
NW1426L	DNT	14,500lm LED (88W)	7,000lm LED (47W)	2	PC	AD AG	ST CH SM SP	CR SQ	
<ul style="list-style-type: none"> • W 14" • HT 32" • OAH 8' (OverAll Height) 									
	DNU	14,500lm LED (88W)	12,000lm LED (100W)	2	PC	AD AG	ST CH SM SP	CR SQ	
	DNW	23,100lm LED (146W)	12,000lm LED (100W)	2	PC	AD AG	ST CH SM SP	CR SQ	
	DHN	6-100W A21 (600W)	1-300W R40 (300W)	2	PC	AD AG	ST CH SM SP	CR SQ	
NW1631L	DOU	14,500lm LED (88W)	12,000lm LED (100W)	2	PC	AD AG	ST CH SM SP	CR SQ	
<ul style="list-style-type: none"> • W 16" • HT 37" • OAH 8' (OverAll Height) 									
	DMB	23,100lm LED (146W)	12,000lm LED (100W)	2	PC	AD AG	ST CH SM SP	CR SQ	
	DGD	29,500lm LED (194W)	12,000lm LED (100W)	2	PC	AD AG	ST CH SM SP	CR SQ	
	DHO	6-100W A21 (600W)	1-300W R40 (300W)	2	PC	AD AG	ST CH SM SP	CR SQ	
NW1836L	DGE	23,500lm LED (131W)	12,000lm LED (100W)	2	PC	AD AG	ST CH SM SP	CR SQ	
<ul style="list-style-type: none"> • W 18" • HT 42" 									

• OAH 10' (OverAll Height)	DNX	37,400lm LED (218W)	12,000lm LED (100W)	2	PC	AD AG	ST CH SM SP	CR SQ
	DHP	9-100W A21 (900W)	1-300W R40 (300W)	2	PC	AD AG	ST CH SM SP	CR SQ
NW2242L	FCB	9-100W A21 (900W)	1-300W R40 (300W)	3	PC	AD AG	ST CH SM SP	CR SQ
<ul style="list-style-type: none"> • W 22" • HT 50" • OAH 10' (OverAll Height) 								

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED or fluorescent lamping
- Wired for dual circuit operation (Body Lamping/Down Lamping)
- High power factor electronic ballast or LED driver
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatability.
- Optional dimming ballast 120V or 277V (LED or fluorescent lamping)
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Dimensions

W	Width
HT	Height
OAH	OverAll Height

Lamps

100W A21	Medium Base, 100W Max, Incandesent or LED
300W R40	300W R40, medium base

Finish Types

PC	Powder Coat
----	-------------

Diffuser Types

AD	Standard Acrylic Diffuser
AG	Premium Glass Diffuser

Mountings

ST	Stem
CH	Chain
SM	Surface Mount Chain
SP	Steep Pitch Canopy for Stem

Louvers

CR	Concentric Ring
SQ	Square Cell

Options

D1	LED 0-10V low voltage control dimming
----	---------------------------------------