# Oak Park Series 2-Arm Cluster Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	
• W 81" • HT 14" • OAH 36" (OverAll Height) • Y 2 @ 24"x10"	EPI	14,300lm LED (116W)	1	PC	WA AG	ST SP MS	
	BSI	8-100W A21 (800W)	1	PC	WA AG	ST SP MS	

### SAMPLE CATALOG NUMBER

## Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

#### PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH Over All Height is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

#### Abbreviation Key

### Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

## Finish Types

PC Powder Coat

#### Diffuser Types

WA Standard Acrylic Diffuser
AG Premium Glass Diffuser

#### Mountings

ST Stem

SP Steep Pitch Canopy for Stem

MS Multi-Stem

# **Dimming Types**

0

D1