


# Oak Park Series 4-Arm Cluster Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
• W 81" • HT 14" • OAH 36" (OverAll Height) • Y 4 @ 24"x10"	EPJ	28,600lm LED (231W)	1	PC	WA AG	ST SP MS
	BST	16-100W A21 (1600W)	1	PC	WA AG	ST SP MS
• W 104" • HT 16" • OAH 48" (OverAll Height) • Y 4 @ 30"x12"	EPK	46,600lm LED (346W)	1	PC	WA AG	ST SP MS
	BSX	16-100W A21 (1600W)	1	PC	WA AG	ST SP MS

# SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



#### PRODUCT FEATURES

· Fabricated and welded metal housing

# Abbreviation Key

## Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

## Finish Types

PC Powder Coat

#### Diffuser Types

WA Standard Acrylic Diffuser
AG Premium Glass Diffuser

#### Mountings

ST Stem

- Powder coated metallic finish
  UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lampingHigh power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
   Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
  • Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

SP Steep Pitch Canopy for Stem

MS Multi-Stem

## **Dimming Types**

D1