


Oak Park Series Pendant



| Model Number                                                               | Lamping Code | Body Lamping        | Circuit | Finish | Diffuser | Mounting       |
|----------------------------------------------------------------------------|--------------|---------------------|---------|--------|----------|----------------|
| <b>OP2410L</b><br><br>• W 24"<br>• HT 10"<br>• OAH 36"<br>(OverAll Height) | ELE          | 7,200lm LED (51W)   | 1       | PC     | WA<br>AG | ST<br>SP<br>MS |
|                                                                            | BQJ          | 4-100W A21 (400W)   | 1       | PC     | WA<br>AG | ST<br>SP<br>MS |
| <b>OP3012L</b><br><br>• W 30"<br>• HT 12"<br>• OAH 36"<br>(OverAll Height) | BQO          | 4-100W A21 (400W)   | 1       | PC     | WA<br>AG | ST<br>SP<br>MS |
|                                                                            |              |                     |         |        |          |                |
| <b>OP3614L</b><br><br>• W 36"<br>• HT 14"<br>• OAH 48"<br>(OverAll Height) | EOA          | 16,500lm LED (135W) | 1       | PC     | WA<br>AG | ST<br>SP<br>MS |
|                                                                            | BQV          | 8-100W A21 (800W)   | 1       | PC     | WA<br>AG | ST<br>SP<br>MS |
| <b>OP4216L</b><br><br>• W 42"<br>• HT 16"<br>• OAH 48"<br>(OverAll Height) | EOD          | 20,400lm LED (159W) | 1       | PC     | WA<br>AG | ST<br>SP<br>MS |
|                                                                            | BRA          | 8-100W A21 (800W)   | 1       | PC     | WA<br>AG | ST<br>SP<br>MS |
| <b>OP4818L</b><br><br>• W 48"<br>• HT 18"<br>• OAH 60"<br>(OverAll Height) | EOE          | 24,700lm LED (202W) | 1       | PC     | WA<br>AG | ST<br>SP<br>MS |
|                                                                            | BRF          | 16-100W A21 (1600W) | 1       | PC     | WA<br>AG | ST<br>SP<br>MS |

Scale



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

100W A21      Medium Base, 100W Max, Incandesent or LED

Finish Types

PC      Powder Coat

Diffuser Types

WA      Standard Acrylic Diffuser

AG      Premium Glass Diffuser

Mountings

ST      Stem

SP      Steep Pitch Canopy for Stem

MS      Multi-Stem

Dimming Types

0      D3

1      D1