

Oak Park Series Wall Bracket



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
OP1812B • W 18" • HT 12"	ELL	2,200lm LED (17W)	1	PC	WA AG	WM
	BSE	1-100W A21 (100W)	1	PC	WA AG	WM
OP2415B • W 24" • HT 15"	ELM	3,500lm LED (28W)	1	PC	WA AG	WM
	BSG	1-100W A21 (100W)	1	PC	WA AG	WM

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 9'
DOOR HEIGHT: 7'
SILHOUETTE HEIGHT: 6'

Abbreviation Key

Lamps

100W A21Medium Base, 100W Max, Incandesent or LED

Finish Types

PCPowder Coat

Diffuser Types

WAStandard Acrylic Diffuser
AGPremium Glass Diffuser

Mountings

WMWall Mount

Dimming Types

- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

0

D1