Craft Metal Products Inc.

2751 N. Emerson Ave.
Indianapolis, IN 46218
(800) 669-3254
(317) 545-3252

# Oak Park Series Wall Sconce




| Model Number | Lamping Code | Body Lamping | Circuit | Finish | Diffuser | Mounting |
|---|---|---|---|---|---|---|
| **OP1808S**<br>• W 18"<br>• HT 8"<br>• EXT 9.5" | EPG | 1,900lm LED (14W) | 1 | PC | WA AG | WM |
| | BSA | 2-100W A21 (200W) | 1 | PC | WA AG | WM |
| **OP2410S**<br>• W 24"<br>• HT 10" | EPH | 3,800lm LED (29W) | 1 | PC | WA AG | WM |
| | BSC | 2-100W A21 (200W) | 1 | PC | WA AG | WM |

SAMPLE CATALOG NUMBER

**Model Number - Lamping Code - Finish - Mounting - Diffuser - Options**

Scale




**PRODUCT FEATURES**

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver

Abbreviation Key

Lamps

| | |
|---|---|
| 100W A21 | Medium Base, 100W Max, Incandesent or LED |

Finish Types

| | |
|---|---|
| PC | Powder Coat |

Diffuser Types

| | |
|---|---|
| WA | Standard Acrylic Diffuser |
| AG | Premium Glass Diffuser |

Mountings

| | |
|---|---|
| WM | Wall Mount |

Dimming Types

- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

0 D1