

Oxford Series Intermediate Pendant



| Model Number                                                                                                     | Lamping Code | Body Lamping       | Down Lamping        | Circuit | Finish | Diffuser | Mounting             | Louver |
|------------------------------------------------------------------------------------------------------------------|--------------|--------------------|---------------------|---------|--------|----------|----------------------|--------|
| OX1418Q <ul style="list-style-type: none"><li>• W 14</li><li>• HT 21</li><li>• OAH 48 (OverAll Height)</li></ul> | DVC          | 6,800lm LED (40W)  | 5,100lm LED (33W)   | 2       | PC     | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ     |
|                                                                                                                  | DKZ          | 6,800lm LED (40W)  | 7,100lm LED (47W)   | 2       | PC     | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ     |
|                                                                                                                  | EGC          | 13,300lm LED (87W) | 5,100lm LED (33W)   | 2       | PC     | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ     |
|                                                                                                                  | EGD          | 13,300lm LED (87W) | 7,100lm LED (47W)   | 2       | PC     | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ     |
|                                                                                                                  | FJZ          | 3-100W A21 (300W)  | 1-100W PAR38 (100W) | 2       | PC     | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ     |

|                                                                      |
|----------------------------------------------------------------------|
| SAMPLE CATALOG NUMBER                                                |
| Model Number - Lamping Code - Finish - Mounting - Diffuser - Options |

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)

|                  |                                           |
|------------------|-------------------------------------------|
| Abbreviation Key |                                           |
| Lamps            |                                           |
| 100W A21         | Medium Base, 100W Max, Incandesent or LED |
| Finish Types     |                                           |
| PC               | Powder Coat                               |
| Diffuser Types   |                                           |
| WA               | Standard Acrylic Diffuser                 |
| AG               | Premium Glass Diffuser                    |
| Mountings        |                                           |

- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

|    |                             |
|----|-----------------------------|
| ST | Stem                        |
| CH | Chain                       |
| SM | Surface Mount Chain         |
| SP | Steep Pitch Canopy for Stem |

Louvers

|    |             |
|----|-------------|
| SQ | Square Cell |
|----|-------------|

Dimming Types

|   |     |
|---|-----|
| 0 | D1  |
| 1 | D2  |
| 2 | D16 |
| 3 | D3  |