

Pasadena Series Wall Bracket



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
PA0816B	ATE	1-100W A21 (100W)	1	PC	WA	WM	SQ	SIL LOGO BL
• W 8" • HT 16" • EXT 11"								
PA1020B	ATG	1-100W A21 (100W)	1	PC	WA	WM	SQ	SIL LOGO BL
• W 10" • HT 20" • EXT 13"								
PA1224B	GBY	2-100W A21 (200W)	1	PC	WA	WM	SQ	SIL LOGO BL
• W 12" • HT 24" • EXT 15"								

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

Mountings

WM Wall Mount

PRODUCT FEATURES

• Fabricated and welded metal housing

• Powder coated metallic finish

• UV stable, white acrylic cylinder diffuser (Standard)

- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Louvers	
SQ	Square Cell
Options	
SIL	Silhouette Symbol
LOGO	Custom Logo
BL	Bottom Lens