

Pasadena Series Wall Sconce



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
PA0816S • W 8" • HT 16" • EXT 4"	DYX	1,000lm LED (7W)	1	PC	WA	WM	BD	SIL BL
	DYY	1,800lm LED (14W)	1	PC	WA	WM	BD	SIL BL
	ASX	1-60W A19 (60W)	1	PC	WA	WM	BD	SIL BL
PA1020S • W 10" • HT 20" • EXT 5"	DYZ	1,800lm LED (14W)	1	PC	WA	WM	BD	SIL BL
	DZA	3,100lm LED (22W)	1	PC	WA	WM	BD	SIL BL
	ASZ	2-100W A21 (200W)	1	PC	WA	WM	BD	SIL BL
PA1224S • W 12" • HT 24" • EXT 6"	DZB	6,300lm LED (40W)	1	PC	WA	WM	BD	SIL BL
	FEH	7,100lm LED (44W)	1	PC	WA	WM	BD	SIL BL
	ATC	3-100W A21 (300W)	1	PC	WA	WM	BD	SIL BL

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 9'
DOOR HEIGHT: 7'
SILHOUETTE HEIGHT: 6'

Abbreviation Key

Lamps

60W A19 Medium Base, 60W Max, Incandesent or LED

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

Mountings

- PRODUCT FEATURES
- Fabricated and welded metal housing

- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

WM	Wall Mount
Louvers	
BD	Bottom Perf Door
Dimming Types	
0	D1
1	D2
Options	
SIL	Silhouette Symbol
BL	Bottom Lens
BD	Bottom Door