

Phoenix Series Intermediate Pendant



Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
PX1218Q • W 12" • HT 18" • OAH 72" (OverAll Height)	EFI	6,800lm LED (40W)	5,100lm LED (33W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	EGX	6,800lm LED (40W)	7,100lm LED (47W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	ENL	13,300lm LED (87W)	5,100lm LED (33W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	ENN	13,300lm LED (87W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

- PRODUCT FEATURES
- Fabricated and welded metal housing
 - Powder coated metallic finish
 - UV stable, white acrylic cylinder diffuser (Standard)
 - Optional specialty diffuser materials available
 - Energy efficient LED lamping
 - High power factor electronic LED driver
 - Wired for dual circuit operation, Body Lamping and Down Lamping
 - Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
 - Standard LED CRI is 80 - contact us for alternate CRI availability
 - Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
 - Standard LED dimming is 0-10v
 - Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
 - Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
 - Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
 - For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
 - UL / cUL or ETL / cETL listed
 - Contact Us for more lamping options.

Abbreviation Key	
Finish Types	
PC	Powder Coat
Diffuser Types	
WA	Standard Acrylic Diffuser
Mountings	
ST	Stem
CH	Chain
SM	Surface Mount Chain
SP	Steep Pitch Canopy for Stem
Louvers	
SQ	Square Cell

Dimming Types

0	D1
1	D2

Options

CUT	Cut-Out Symbol
LOGO	Custom Logo