

Phoenix Series Pendant




Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
PX1024L • W 10" • HT 24" • OAH 72" (OverAll Height)	GEK	4-60W A19 (240W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
PX1226L • W 12" • HT 26" • OAH 96" (OverAll Height)	DVI	14,500lm LED (86W)	5,100lm LED (36W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	DOC	14,500lm LED (86W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	DOD	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	DOF	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	FJC	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
PX1231L • W 12" • HT 31" • OAH 96" (OverAll Height)	EFJ	14,500lm LED (86W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	DOT	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	DMJ	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	DLP	29,500lm LED (192W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	FJD	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA	ST	SQ	CUT

							CH SM SP		LOGO
PX1236L • W 12" • HT 36" • OAH 96" (OverAll Height)	GLF	15,400lm LED (86W)	5,100lm LED (33W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	GJF	24,900lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	GKI	33,700lm LED (224W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	GIY	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

- | | |
|------------|--|
| 60W A19 | Medium Base, 60W Max, Incandescent or LED |
| 100W PAR38 | Medium Base, 100W Max, Incandescent or LED |

Finish Types

- | | |
|----|-------------|
| PC | Powder Coat |
|----|-------------|

Diffuser Types

- | | |
|----|---------------------------|
| WA | Standard Acrylic Diffuser |
|----|---------------------------|

Mountings

- | | |
|----|-----------------------------|
| ST | Stem |
| CH | Chain |
| SM | Surface Mount Chain |
| SP | Steep Pitch Canopy for Stem |

Louvers

- | | |
|----|-------------|
| SQ | Square Cell |
|----|-------------|

Dimming Types

- | | |
|---|----|
| 0 | D1 |
| 1 | D2 |
| 2 | D3 |

Options

- | | |
|------|----------------|
| CUT | Cut-Out Symbol |
| LOGO | Custom Logo |