

Phoenix Series Wall Bracket



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
PX0816B	ATE	1-100W A21 (100W)	1	PC	WA	WM	SQ	CUT LOGO BL
• W 8" • HT 16" • EXT 11"								
PX1020B	ATG	1-100W A21 (100W)	1	PC	WA	WM	SQ	CUT LOGO BL
• W 10" • HT 20" • EXT 13"								
PX1224B	GBY	2-100W A21 (200W)	1	PC	WA	WM	SQ	CUT LOGO BL
• W 12" • HT 24" • EXT 15"								

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 9'

DOOR HEIGHT: 7'

SILHOUETTE HEIGHT: 6'

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

Mountings

WM Wall Mount

PRODUCT FEATURES

• Fabricated and welded metal housing

• Powder coated metallic finish

• UV stable, white acrylic cylinder diffuser (Standard)

- Optional specialty diffuser materials available
- Energy efficient LED lighting
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lighting
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lighting is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lighting options.

Louvers	
SQ	Square Cell
Options	
CUT	Cut-Out Symbol
LOGO	Custom Logo
BL	Bottom Lens