



Randolph Series 2-Tier Large Pendant



Model Number	Lamping Code	Gallery Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver
RD2412W • W 24 • HT 13 • OAH 48 (OverAll Height)	GFK	11,900lm LED (77W)		1	PC	WA AG	TC	SQ
	GLK	6-60W A19 (360W)	1-100W R40/Par38 (100W)	2	PC	WA AG	TC	SQ
RD3014W • W 30 • HT 15 • OAH 72 (OverAll Height)	GFP	18,700lm LED (135W)		1	PC	WA AG	TC	SQ
	GLL	6-60W A19 (360W)	1-100W R40/Par38 (100W)	2	PC	WA AG	TC	SQ
RD3616W • W 36 • HT 18 • OAH 96 (OverAll Height)	DWC	35,200lm LED (216W)	7,100lm LED (51W)	2	PC	WA AG	TC	SQ
	DJP	6-100W A21 (600W)	1-100W R40/Par38 (100W)	2	PC	WA AG	TC	SQ
RD4218W • W 42 • HT 20 • OAH 96 (OverAll Height)	DWF	35,200lm LED (216W)	12,500lm LED (93W)	2	PC	WA AG	TC	SQ
	DJQ	12-100W A21 (1200W)	1-100W R40/Par38 (100W)	2	PC	WA AG	TC	SQ
RD5422W • W 54 • HT 24 • OAH 120 (OverAll Height)	EYG	42,200lm LED (260W)	12,500lm LED (93W)	2	PC	WA AG	TC	SQ
	EYJ	12-100W A21 (1200W)	1-100W R40/Par38 (100W)	2	PC	WA AG	TC	SQ



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Gallery Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key	
Lamps	
60W A19	Medium Base, 60W Max, Incandescent or LED
100W R40/Par38	Medium Base, 100W Max, Incandescent or LED
Finish Types	
PC	Powder Coat
Diffuser Types	
WA	Standard Acrylic Diffuser
AG	Premium Glass Diffuser
Mountings	
TC	Triple Chain Spreader
Louvers	
SQ	Square Cell
Dimming Types	
0	D1