Craft Metal Products Inc.

2751 N. Emerson Ave.
Indianapolis, IN 46218
(800) 669-3254
(317) 545-3252

Randolph Series Wall Bracket





Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver
RD0816B • W 8 • HT 18 • EXT 10	DEH	2,100lm LED (16W)	1	PC	WA AG	WM	SQ
	ANP	1-100W A21 (100W)	1	PC	WA AG	WM	SQ
RD1020B • W 10 • HT 23 • EXT 12	DAG	3,100lm LED (22W)	1	PC	WA AG	WM	SQ
	ANR	1-100W A21 (100W)	1	PC	WA AG	WM	SQ
RD1224B • W 12 • HT 27 • EXT 14	FEL	4,400lm LED (33W)	1	PC	WA AG	WM	SQ
	FEK	1-100W A21 (100W)	1	PC	WA AG	WM	SQ
RD1426B • W 14 • HT 30 • EXT 16	DEK	6,300lm LED (47W)	1	PC	WA AG	WM	SQ
	ANW	2-100W A21 (200W)	1	PC	WA AG	WM	SQ

SAMPLE CATALOG NUMBER


Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

Abbreviation Key

Lamps

100W A21	Medium Base, 100W Max, Incandesent or LED



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Finish Types	
PC	Powder Coat

Diffuser Types	
WA	Standard Acrylic Diffuser
AG	Premium Glass Diffuser

Mountings	
WM	Wall Mount

Louvers	
SQ	Square Cell

Dimming Types	
0	D1
1	D3