

Rockford Series Intermediate Pendant



Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
RF1218Q • W 14 • HT 18 • OAH 48 (OverAll Height)	DVT	6,800lm LED (40W)	5,100lm LED (33W)	2	PC	WA	ST CH SM SP	SQ	SIL
	DKX	6,800lm LED (40W)	7,100lm LED (47W)	2	PC	WA	ST CH SM SP	SQ	SIL
	EFY	13,300lm LED (87W)	5,100lm LED (33W)	2	PC	WA	ST CH SM SP	SQ	SIL
	EFZ	13,300lm LED (87W)	7,100lm LED (47W)	2	PC	WA	ST CH SM SP	SQ	SIL
	DGH	3-60W A19 (180W)	1-100W A19 (100W)	2	PC	WA	ST CH SM SP	SQ	SIL

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)

Abbreviation Key	
Lamps	
60W A19	Medium Base, 60W Max, Incandesent or LED
100W A19	Medium Base, 100W Max, Incandesent or LED
Finish Types	
PC	Powder Coat
Diffuser Types	
WA	Standard Acrylic Diffuser
Mountings	
ST	Stem

- UL / cUL or ETL / cETL listed
- Contact Us for more lighting options.

CH	Chain
SM	Surface Mount Chain
SP	Steep Pitch Canopy for Stem

Louvers	
SQ	Square Cell

Dimming Types	
0	D1
1	D2
2	D7
3	D3

Options	
SIL	Silhouette Symbol