

Rockford Series Wall Bracket



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
RF0816B	AHZ	1-100W A21 (100W)	1	PC	WA	WM	SQ	SIL BL
	• W 8"							
	• HT 16"							
	• EXT 11"							
RF1020B	DEM	3,900lm LED (24W)	1	PC	WA	WM	SQ	SIL BL
	• W 10"							
	AIB	1-100W A21 (100W)	1	PC	WA	WM	SQ	SIL BL
RF1224B	FFX	5,400lm LED (33W)	1	PC	WA	WM	SQ	SIL BL
	• W 12"							
	GBW	2-100W A21 (200W)	1	PC	WA	WM	SQ	SIL BL
• HT 24"								
• EXT 15"								

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 9'
DOOR HEIGHT: 7'
SILHOUETTE HEIGHT: 6'

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

Mountings

WM Wall Mount

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)

- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Louvers	
SQ	Square Cell
Dimming Types	
0	D1
2	D3
Options	
SIL	Silhouette Symbol
BL	Bottom Lens