

Reno Series Pendant



Model Number	Lamping Code	Body Lamping				Circuit	Finish	Diffuser	Mounting	Options
• W 30" • HT 12" • OAH 36" (OverAll Height)	EZV		4	,800lm LED (33V	V)	1	PC	LS	ST SP	BL
	EZU		8	,700lm LED (65V	V)	1	PC	LS	ST SP	BL
RN3612L • W 36" • HT 12" • OAH 36" (OverAll Height)	EZW		3	,700lm LED (60V	V)	1	PC	LS	ST SP	BL
RN4215L • W 42" • HT 15"	EZX		1	1,600lm LED (94)	N)	1	PC	LS	ST SP	BL

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

• OAH 36" (OverAll Height)

- Fabricated and welded metal housing
- Powder coated metallic finish
- Easy to clean encapsulated fabric diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)

Abbreviation Key

Finish Types

PC Powder Coat

Diffuser Types

LS Lamp Shade Diffuser

Mountings

ST Sten

SP Steep Pitch Canopy for Stem

- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
 For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
 UL / cUL or ETL / cETL listed
 Contact Us for more lamping options.

Dimming Types

0 D1

1 D2

Options

 BL Bottom Lens