

## Reno Series Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Options
<b>RN3012L</b>	EZV	4,800lm LED (33W)	1	PC	LS	ST SP	BL D1 D2
<ul style="list-style-type: none"> <li>• W 30</li> <li>• HT 12</li> <li>• OAH 36 (OverAll Height)</li> </ul>	EZU	8,700lm LED (60W)	1	PC	LS	ST SP	BL D1 D2
<b>RN3612L</b>	EZW	8,700lm LED (60W)	1	PC	LS	ST SP	BL D1 D2
<ul style="list-style-type: none"> <li>• W 36</li> <li>• HT 12</li> <li>• OAH 36 (OverAll Height)</li> </ul>							
<b>RN4215L</b>	EZX	11,600lm LED (86W)	1	PC	LS	ST SP	BL D1 D2
<ul style="list-style-type: none"> <li>• W 42</li> <li>• HT 15</li> <li>• OAH 36 (OverAll Height)</li> </ul>							

### SAMPLE CATALOG NUMBER

**Model Number - Lamping Code - Finish - Mounting - Diffuser - Options**

### PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white glass diffuser(Standard)
- Optional specialty diffuser materials available
- Energy efficient LED
- Wired for single circuit operation (Body Lamping)
- High power factor electronic LED driver
- Standard LED color temperature is 3000K with 80 CRI. Contact us for other color temperature or CRI options.
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatability.
- Optional dimming driver 120V or 277V (LED lamping)
- Fixture is Stem or Aircraft Cable hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter

### Abbreviation Key

#### Finish Types

PC Powder Coat

#### Diffuser Types

LS Lamp Shade Diffuser

#### Mountings

ST Stem

SP Steep Pitch Canopy for Stem

(Stem only)

- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

#### Dimming

D1	LED 0-10v dimming options include integral 120-277v dimming drivers
D2	LED Triac/ELV dimming options include integral 120v dimming drivers

#### Options

BL	Bottom Lens
----	-------------