

Riverside Series Ceiling Mount





Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Diffuser Accent	Mounting	Louver	Options
RS1007C • W 11 • HT 10	АНО	2-100W A21 (200W)	1	PC	WA	DAC CDA	СС	SQ	SIL LOGO
RS1208C • W 13 • HT 11	GJJ	5,400lm LED (33W)	1	PC	WA	DAC CDA	CC	SQ	SIL LOGO
	AHQ	3-100W A21 (300W)	1	PC	WA	DAC	СС	SQ	SIL

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- Fabricated and welded metal housing
- · Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

Diffuser Accent Types

DAC Diffuser Accent Color
CDA Custom Diffuser Accent

Mountings

CC Ceiling Canopy

Louvers

SQ Square Cell

- manufacturer for compatibility.

 Standard LED dimming is 0-10v

 Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility

 Mounts to standard electrical junction box (by others)

 UL / cUL or ETL / cETL listed

 Contact Us for more lamping options.

Dimming Types

D1 0 1 D2

Options

SIL Silhouette Symbol LOGO Custom Logo