

Riverside Series Intermediate Pendant



Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Diffuser Accent	Mounting	Louver	Options
RS1218Q • W 13 • HT 18 • OAH 48 (OverAll Height)	DVT	6,800lm LED (40W)	5,100lm LED (33W)	2	PC	WA	DAC CDA	ST CH SM SP	SQ	SIL LOGO
	DKX	6,800lm LED (40W)	7,100lm LED (47W)	2	PC	WA	DAC CDA	ST CH SM SP	SQ	SIL LOGO
	EFY	13,300lm LED (87W)	5,100lm LED (33W)	2	PC	WA	DAC CDA	ST CH SM SP	SQ	SIL LOGO
	EFZ	13,300lm LED (87W)	7,100lm LED (47W)	2	PC	WA	DAC CDA	ST CH SM SP	SQ	SIL LOGO
	DGH	3-60W A19 (180W)	1-100W A19 (100W)	2	PC	WA	DAC CDA	ST CH SM SP	SQ	SIL LOGO

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- · Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)

Abbreviation Key

Lamps

60W A19 Medium Base, 60W Max, Incandesent or LED
100W A19 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

Diffuser Accent Types

DAC Diffuser Accent Color

- UL / cUL or ETL / cETL listed Contact Us for more lamping options.

CDA Custom Diffuser Accent

Mountings

ST Stem СН Chain

Surface Mount Chain SM

SP Steep Pitch Canopy for Stem

Louvers

SQ Square Cell

Dimming Types

0 D1 1 D2 2 D7 3 D3

Options

SIL Silhouette Symbol LOGO Custom Logo