


Roxbury Series Pendant



Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver
RX1024L	GBK	4-60W A19 (240W)	1-100W PAR38 (100W)	2	PC	AD	ST CH SM SP	SQ
<ul style="list-style-type: none"> • W 10 • HT 31 • OAH 72 (OverAll Height) 								
RX1226L	DVD	14,500lm LED (86W)	5,100lm LED (33W)	2	PC	AD	ST CH SM SP	SQ
<ul style="list-style-type: none"> • W 12 • HT 34 • OAH 96 (OverAll Height) 								
	DNY	14,500lm LED (86W)	7,100lm LED (47W)	2	PC	AD	ST CH SM SP	SQ
	DNZ	14,500lm LED (86W)	12,500lm LED (85W)	2	PC	AD	ST CH SM SP	SQ
	DOA	23,100lm LED (146W)	7,100lm LED (47W)	2	PC	AD	ST CH SM SP	SQ
	ETG	23,100lm LED (146W)	10,400lm LED (70W)	2	PC	AD	ST CH SM SP	SQ
	DOB	23,100lm LED (146W)	12,500lm LED (85W)	2	PC	AD	ST CH	SQ

	FIY	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	AD	ST CH SM SP	SQ
RX1231L	DXL	14,500lm LED (86W)	7,100lm LED (47W)	2	PC	AD	ST CH SM SP	SQ
• W 12 • HT 39 • OAH 96 (OverAll Height)	DOS	14,500lm LED (86W)	12,500lm LED (85W)	2	PC	AD	ST CH SM SP	SQ
	DMF	23,100lm LED (146W)	12,500lm LED (85W)	2	PC	AD	ST CH SM SP	SQ
	DKO	29,500lm LED (192W)	12,500lm LED (85W)	2	PC	AD	ST CH SM SP	SQ
	FIZ	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	AD	ST CH SM SP	SQ
RX1236L	GKG	10,800lm LED (66W)		1	PC	AD	ST CH SM SP	SQ
• W 12 • HT 44 • OAH 96 (OverAll Height)	GDZ	15,400lm LED (93W)	5,100lm LED (33W)	2	PC	AD	ST CH SM SP	SQ
	GEF	17,900lm LED (113W)	12,500lm LED (85W)	2	PC	AD	ST CH SM SP	SQ
	GES	24,900lm LED (159W)	12,500lm LED (85W)	2	PC	AD	ST CH SM SP	SQ
	GEV	33,800lm LED (231W)	12,500lm LED (85W)	2	PC	AD	ST CH SM SP	SQ
	GIX	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	AD	ST CH SM SP	SQ

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options


Scale

Abbreviation Key

Lamps

- 60W A19 Medium Base, 60W Max, Incandesent or LED
- 100W PAR38 Medium Base, 100W Max, Incandesent or LED

Finish Types



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

PC Powder Coat

Diffuser Types

AD Standard Acrylic Diffuser

Mountings

ST Stem

CH Chain

SM Surface Mount Chain

SP Steep Pitch Canopy for Stem

Louvers

SQ Square Cell

Dimming Types

0 D1

1 D2

2 D3