

San Antonio Series Ceiling Mount






Model Number	Lamping Body Lamping Code		Circuit I	Finish	Diffuser	Mounting
SA1806C • W 18"	EDX	2,600lm LED (22W)	1	PC	WA PA	CC FM
• HT 9"						
	BCR	2-60W A19 (120W)	1	PC	WA PA	CC FM
SA2408C	EDY	2,600lm LED (22W)	1	PC	WA PA	CC FM
• W 24" • HT 11"					FA	1 1*1
	GHC	5,400lm LED (39W)	1	PC	WA PA	CC FM
	EOO	7,700lm LED (53W)	1	PC	WA PA	CC FM
	ВСТ	3-60W A19 (180W)	1	PC	WA PA	CC FM
SA3010C	EOP	7,700lm LED (58W)	1	PC	WA	CC
• W 30" • HT 12"					PA	FM
	EOQ	13,600lm LED (96W)	1	PC	WA PA	CC FM
	BHR	3-100W A21 (300W)	1	PC	WA PA	CC FM
SA3612C	EOR	16,500lm LED (101W)	1	PC	WA	CC
• W 36" • HT 13"					PA	FM
	ВНТ	3-100W A21 (300W)	1	PC	WA PA	CC FM

SA4214C	EOT	23,400lm LED (159W)	1	PC	WA PA	CC FM
• W 42" • HT 15"						
	FJU	6-60W A19 (360W)	1	PC	WA PA	CC FM

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale



PRODUCT FEATURES

- Fabricated and welded metal housing
- · Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- · Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19 Medium Base, 60W Max, Incandesent or LED
100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser
PA Premium Acrylic Diffuser

Mountings

CC Ceiling Canopy
FM Flush Mount

Dimming Types

0 D1