

San Antonio Series Ceiling Mount



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
SA1806C • W 18" • HT 9"	EDX	2,600lm LED (22W)	1	PC	WA PA	CC FM
	BCR	2-60W A19 (120W)	1	PC	WA PA	CC FM
SA2408C • W 24" • HT 11"	EDY	2,600lm LED (22W)	1	PC	WA PA	CC FM
	GHC	5,400lm LED (39W)	1	PC	WA PA	CC FM
	EOO	7,700lm LED (53W)	1	PC	WA PA	CC FM
	BCT	3-60W A19 (180W)	1	PC	WA PA	CC FM
SA3010C • W 30" • HT 12"	EOP	7,700lm LED (58W)	1	PC	WA PA	CC FM
	EOQ	13,600lm LED (96W)	1	PC	WA PA	CC FM
	BHR	3-100W A21 (300W)	1	PC	WA PA	CC FM
SA3612C • W 36" • HT 13"	EOR	16,500lm LED (101W)	1	PC	WA PA	CC FM
	BHT	3-100W A21 (300W)	1	PC	WA PA	CC FM

SA4214C	EOT	23,400lm LED (159W)	1	PC	WA PA	CC FM
	FJU	6-60W A19 (360W)	1	PC	WA PA	CC FM

- W 42"
- HT 15"

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 9'
DOOR HEIGHT: 7'
SILHOUETTE HEIGHT: 6'

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19

Medium Base, 60W Max, Incandesent or LED

100W A21

Medium Base, 100W Max, Incandesent or LED

Finish Types

PC

Powder Coat

Diffuser Types

WA

Standard Acrylic Diffuser

PA

Premium Acrylic Diffuser

Mountings

CC

Ceiling Canopy

FM

Flush Mount

Dimming Types

0

D1