

Sacramento Series 4-Arm Cluster Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
SC5012V • W 72" • HT 12" • OAH 36" (OverAll Height) • Y 4 @ 24"x8"	ENA	31,000lm LED (231W)	1	PC	WA PA	ST SP MS
	EOY	49,000lm LED (384W)	1	PC	WA PA	ST SP MS
	BDV	16-60W A19 (960W)	1	PC	WA PA	ST SP MS
SC6214V • W 90" • HT 14" • OAH 48" (OverAll Height) • Y 4 @ 30"x10"	ENB	37,000lm LED (231W)	1	PC	WA PA	ST SP MS
	EOZ	54,600lm LED (384W)	1	PC	WA PA	ST SP MS
	BDZ	24-100W A21 (2400W)	1	PC	WA PA	ST SP MS

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES • Fabricated and welded metal housing • Powder coated metallic finish • UV stable, white acrylic bowl diffuser (Standard) • Optional specialty diffuser materials available • Energy efficient LED lamping • High power factor electronic LED driver • Wired for dual circuit operation, Body Lamping and Down Lamping • Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability • Standard LED CRI is 80 - contact us for alternate CRI availability • Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility. • Standard LED dimming is 0-10v • Optional line voltage (Triac or ELV) LED dimming is available - consult for	Abbreviation Key
	Lamps
	60W A19 Medium Base, 60W Max, Incandesent or LED
	100W A21 Medium Base, 100W Max, Incandesent or LED
	Finish Types
	PC Powder Coat
	Diffuser Types

- compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

WA	Standard Acrylic Diffuser
PA	Premium Acrylic Diffuser

Mountings	
ST	Stem
SP	Steep Pitch Canopy for Stem
MS	Multi-Stem

Dimming Types	
0	D1