


Sacramento Series Wall Bracket



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
SC1814B	EMQ	3,200lm LED (20W)	1	PC	WA PA	WM
	• W 18" • HT 14"					
	BCZ	1-100W A21 (100W)	1	PC	WA PA	WM
SC2417B	EMR	3,200lm LED (20W)	1	PC	WA PA	WM
	• W 24" • HT 17"					
	BDB	1-100W A21 (100W)	1	PC	WA PA	WM

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature

Abbreviation Key

Lamps	
100W A21	Medium Base, 100W Max, Incandesent or LED
Finish Types	
PC	Powder Coat
Diffuser Types	
WA	Standard Acrylic Diffuser
PA	Premium Acrylic Diffuser
Mountings	
WM	Wall Mount
Dimming Types	

availability

- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

0

D1