

San Francisco Series 4-Arm Cluster Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
• W 78 • HT 14 • OAH 36 (OverAll Height) • X 4 @ 30"x10"	EBW	31,000lm LED (231W)	1	PC	WA PA	ST SP MS
	EBX	49,000lm LED (384W)	1	PC	WA PA	ST SP MS
	BGD	16-100W A21 (1600W)	1	PC	WA PA	ST SP MS
• W 96 • HT 16 • OAH 48 (OverAll Height) • Y 4 @ 36"x12"	ECA	37,000lm LED (231W)	1	PC	WA PA	ST SP MS
	DWY	54,600lm LED (384W)	1	PC	WA PA	ST SP MS
	BGH	24-100W A21 (2400W)	1	PC	WA PA	ST SP MS

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

- compatibility

 Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH Over All Height is the length from the ceiling to the bottom of the fixture.)

 Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)

 For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)

 UL / cUL or ETL / cETL listed

 Contact Us for more lamping options.

PA Premium Acrylic Diffuser

Mountings

ST Stem

SP Steep Pitch Canopy for Stem

Multi-Stem MS

Dimming Types

0 D1