

San Francisco Series 4-Arm Cluster Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
SF5012V • W 78 • HT 14 • OAH 36 (OverAll Height) • X 4 @ 30"x10"	EBW	31,000lm LED (231W)	1	PC	WA PA	ST SP MS
	EBX	49,000lm LED (384W)	1	PC	WA PA	ST SP MS
	BGD	16-100W A21 (1600W)	1	PC	WA PA	ST SP MS
SF6214V • W 96 • HT 16 • OAH 48 (OverAll Height) • Y 4 @ 36"x12"	ECA	37,000lm LED (231W)	1	PC	WA PA	ST SP MS
	DWY	54,600lm LED (384W)	1	PC	WA PA	ST SP MS
	BGH	24-100W A21 (2400W)	1	PC	WA PA	ST SP MS

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

- compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

PA Premium Acrylic Diffuser

Mountings

ST	Stem
SP	Steep Pitch Canopy for Stem
MS	Multi-Stem

Dimming Types

0	D1
---	----