

San Francisco Series Ceiling Mount





Model Number	Lamping Code	Body Lamping	Up Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting
5510055	FD./	2 (201) 1 FD (2010)				D.C.	10/0	66
SF1806C	EDV	2,600lm LED (22W)			1	PC	WA PA	CC FM
• W 18" • HT 9"								
	BEZ	2-60W A19 (120W)			1	PC	WA PA	CC FM
SF2409C	EDW	3,800lm LED (31W)			1	PC	WA PA	CC FM
• W 24" • HT 12"							PA	ΓIVI
	BFB	3-60W A19 (180W)			1	PC	WA PA	CC FM
SF3010C	ETA	9,600lm LED (70W)	3,200lm LED	6,400lm LED	1	PC	WA PA	CC FM
• W 30" • HT 13"							FA	FIMI
	ВНІ	3-100W A21 (300W)			1	PC	WA PA	CC FM
SF3612C	ETB	16,400lm LED (119W)	10,900lm LED	5,400lm LED	1	PC	WA	CC
• W 36" • HT 15"							PA	FM
	BHL	3-100W A21 (300W)			1	PC	WA PA	CC FM
SF4214C	ETC	19,000lm LED (132W)	14,200lm LED	4,700lm LED	1	PC	WA PA	CC FM
• W 42" • HT 17"							PA	FΙVΙ
	FJQ	6-60W A19 (360W)			1	PC	WA PA	CC FM

Scale



PRODUCT FEATURES

- · Fabricated and welded metal housing
- Powder coated metallic finishUV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
 Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19 Medium Base, 60W Max, Incandesent or LED 100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC **Powder Coat**

Diffuser Types

WA Standard Acrylic Diffuser PΑ Premium Acrylic Diffuser

Mountings

CC Ceiling Canopy FΜ Flush Mount

Dimming Types

D1