
Craft Metal Products Inc.

2751 N. Emerson Ave.
Indianapolis, IN 46218
(800) 669-3254
(317) 545-3252

St. Louis Series Pendant






Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
SL2407L • W 25 • HT 8 • OAH 36 (OverAll Height)	FVT	5,100lm LED (39W)	1	PC	WA PA	ST SP MS
SL3008L • W 31 • HT 9 • OAH 48 (OverAll Height)	FVV	7,700lm LED (58W)	1	PC	WA PA	ST SP MS
	FVW	13,600lm LED (96W)	1	PC	WA PA	ST SP MS
SL4210L • W 43 • HT 11 • OAH 72 (OverAll Height)	FVZ	23,400lm LED (146W)	1	PC	WA PA	ST SP MS
	FWA	34,400lm LED (225W)	1	PC	WA PA	ST SP MS

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale



Abbreviation Key

Finish Types

PC	Powder Coat

Diffuser Types

WA	Standard Acrylic Diffuser
PA	Premium Acrylic Diffuser

Mountings

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

ST	Stem
SP	Steep Pitch Canopy for Stem
MS	Multi-Stem

Dimming Types	
0	D1