

Spokane Series 3-Arm Cluster Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Options
SP5015U • W 72 • HT 15 • OAH 36 (OverAll Height)	EVX	23,200lm LED (159W)	1	PC	AD PA	ST SP MS	D1 FD
	EVY	30,500lm LED (212W)	1	PC	AD PA	ST SP MS	D1 FD
	EWI	12-100W A21 (1200W)	1	PC	AD PA	ST SP MS	FD
SP6217U • W 90 • HT 17 • OAH 48 (OverAll Height)	EVZ	27,700lm LED (159W)	1	PC	AD PA	ST SP MS	D1 FD
	EWA	37,900lm LED (264W)	1	PC	AD PA	ST SP MS	D1 FD
	EWJ	18-100W A21 (1800W)	1	PC	AD PA	ST SP MS	FD

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED or fluorescent lamping
- Wired for dual circuit operation (Body Lamping/Down Lamping)
- High power factor electronic ballast or LED driver
- Standard LED color temperature is 3000K with 80 CRI. Contact us for other color temperature or CRI options.
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatability.
- Optional dimming ballast 120V or 277V (LED or fluorescent lamping)
- Fixture may be Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard 4" octagonal electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

AD Standard Acrylic Diffuser
PA Premium Acrylic Diffuser

Mountings

ST Stem
SP Steep Pitch Canopy for Stem

MS Multi-Stem

Dimming Types

0 D1

Options

FD Frosted Diffuser