

Spokane Series 4-Arm Cluster Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Options
SP5015V • W 72 • HT 15 • OAH 36 (OverAll Height)	EWB	31,000lm LED (212W)	1	PC	AD PA	ST SP MS	D1 FD
	EWC	49,000lm LED (352W)	1	PC	AD PA	ST SP MS	D1 FD
	EWK	16-100W A21 (1600W)	1	PC	AD PA	ST SP MS	FD
SP6217V • W 90 • HT 17 • OAH 48 (OverAll Height)	EWD	37,000lm LED (212W)	1	PC	AD PA	ST SP MS	D1 FD
	EWE	54,600lm LED (352W)	1	PC	AD PA	ST SP MS	D1 FD
	EWL	24-100W A21 (2400W)	1	PC	AD PA	ST SP MS	FD

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatability.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatability
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

AD Standard Acrylic Diffuser
 PA Premium Acrylic Diffuser

Mountings

ST Stem
 SP Steep Pitch Canopy for Stem

- [Contact Us](#) for more lamping options.

MS

Multi-Stem

Dimming Types

0

D1

Options

FD

Frosted Diffuser