

Spokane Series 4-Arm Cluster Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Options
SP5015V • W 72" • HT 15" • OAH 36" (OverAll Height)	EWB	31,400lm LED (191W)	1	PC	AD PA	ST MS SP	D1 FD
	EWC	49,300lm LED (317W)	1	PC	AD PA	ST MS SP	D1 FD
	EWK	16-100W A21 (1600W)	1	PC	AD PA	ST MS SP	FD
SP6217V • W 90" • HT 17" • OAH 48" (OverAll Height)	EWD	37,400lm LED (233W)	1	PC	AD PA	ST MS SP	D1 FD
	EWE	55,100lm LED (360W)	1	PC	AD PA	ST MS SP	D1 FD
	EWL	24-100W A21 (2400W)	1	PC	AD PA	ST MS SP	FD

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED or fluorescent lamping
- Wired for dual circuit operation (Body Lamping/Down Lamping)
- High power factor electronic ballast or LED driver
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatability.
- Optional dimming ballast 120V or 277V (LED or fluorescent lamping)
- Fixture may be Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard 4" octagonal electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Dimensions

W	Width
HT	Height
OAH	OverAll Height

Lamps

100W A21	Medium Base, 100W Max, Incandesent or LED
----------	---

Finish Types

PC	Powder Coat
----	-------------

Diffuser Types

AD	Standard Acrylic Diffuser
----	---------------------------

PA Premium Acrylic Diffuser

Mountings

ST Stem
MS Multi-Stem
SP Steep Pitch Canopy for Stem

Options

FD Frosted Diffuser
D1 LED 0-10V low voltage control dimming