

Spokane Series Ceiling Mount



Model Number	Lamping Code	Body Lamping	Up Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting
SP1808C	EHP	2,600lm LED (22W)			1	PC	WA PA	CC FM
• W 18" • HT 11"							10	
	EHN	2-60W A19 (120W)			1	PC	WA PA	CC FM
SP2410C	EHS	3,800lm LED (31W)			1	PC	WA PA	CC FM
• W 24" • HT 13"							IA	
	EHQ	3-60W A19 (180W)			1	PC	WA PA	CC FM
SP3013C	FBS	9,600lm LED (70W)	3,200lm LED	6,400lm LED	1	PC	WA PA	CC FM
• W 30" • HT 16"							FA	1 141
	EHT	3-100W A21 (300W)			1	PC	WA PA	CC FM
SP3615C	FBV	16,400lm LED (119W)	10,900lm LED	5,400lm LED	1	PC	WA PA	CC FM
• W 36" • HT 18"							17	1171
	EHV	3-100W A21 (300W)			1	PC	WA PA	CC FM
SP4218C	FBW	19,000lm LED (132W)	14,200lm LED	4,700lm LED	1	PC	WA PA	CC FM
• W 42" • HT 21"								
	FJV	6-60W A19 (360W)			1	PC	WA PA	CC FM

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19 Medium Base, 60W Max, Incandesent or LED
100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser
PA Premium Acrylic Diffuser

Mountings

CC Ceiling Canopy
FM Flush Mount

Dimming Types

D1