

Spokane Series Ceiling Mount



| Model Number                                                                     | Lamping Code | Body Lamping        | Up Lamping   | Down Lamping | Circuit | Finish | Diffuser | Mounting |
|----------------------------------------------------------------------------------|--------------|---------------------|--------------|--------------|---------|--------|----------|----------|
| SP1808C <ul style="list-style-type: none"><li>• W 18"</li><li>• HT 11"</li></ul> | EHP          | 2,600lm LED (22W)   |              |              | 1       | PC     | WA<br>PA | CC<br>FM |
|                                                                                  | EHN          | 2-60W A19 (120W)    |              |              | 1       | PC     | WA<br>PA | CC<br>FM |
| SP2410C <ul style="list-style-type: none"><li>• W 24"</li><li>• HT 13"</li></ul> | EHS          | 3,800lm LED (31W)   |              |              | 1       | PC     | WA<br>PA | CC<br>FM |
|                                                                                  | EHQ          | 3-60W A19 (180W)    |              |              | 1       | PC     | WA<br>PA | CC<br>FM |
| SP3013C <ul style="list-style-type: none"><li>• W 30"</li><li>• HT 16"</li></ul> | FBS          | 9,600lm LED (70W)   | 3,200lm LED  | 6,400lm LED  | 1       | PC     | WA<br>PA | CC<br>FM |
|                                                                                  | EHT          | 3-100W A21 (300W)   |              |              | 1       | PC     | WA<br>PA | CC<br>FM |
| SP3615C <ul style="list-style-type: none"><li>• W 36"</li><li>• HT 18"</li></ul> | FBV          | 16,400lm LED (119W) | 10,900lm LED | 5,400lm LED  | 1       | PC     | WA<br>PA | CC<br>FM |
|                                                                                  | EHV          | 3-100W A21 (300W)   |              |              | 1       | PC     | WA<br>PA | CC<br>FM |
| SP4218C <ul style="list-style-type: none"><li>• W 42"</li><li>• HT 21"</li></ul> | FBW          | 19,000lm LED (132W) | 14,200lm LED | 4,700lm LED  | 1       | PC     | WA<br>PA | CC<br>FM |
|                                                                                  | FJV          | 6-60W A19 (360W)    |              |              | 1       | PC     | WA<br>PA | CC<br>FM |

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

|          |                                            |
|----------|--------------------------------------------|
| 60W A19  | Medium Base, 60W Max, Incandescent or LED  |
| 100W A21 | Medium Base, 100W Max, Incandescent or LED |

Finish Types

|    |             |
|----|-------------|
| PC | Powder Coat |
|----|-------------|

Diffuser Types

|    |                           |
|----|---------------------------|
| WA | Standard Acrylic Diffuser |
| PA | Premium Acrylic Diffuser  |

Mountings

|    |                |
|----|----------------|
| CC | Ceiling Canopy |
| FM | Flush Mount    |

Dimming Types

|   |    |
|---|----|
| 0 | D1 |
|---|----|