

## Spokane Series Pedestal Mount



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Options
<b>SP1815M</b>	FBY	1-100W A21 (100W)	1	PC	AD PA	FD

- W 18
- HT 15

### SAMPLE CATALOG NUMBER

**Model Number - Lamping Code - Finish - Mounting - Diffuser - Options**

### PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED or fluorescent lamping
- Wired for single circuit operation (Body Lamping)
- High power factor electronic ballast or LED driver
- Standard LED color temperature is 3000K with 80 CRI. Contact us for other color temperature or CRI options.
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatability.
- Optional dimming ballast 120V or 277V (LED or fluorescent lamping)
- Mounts to standard 4" octagonal electrical junction box (by others)
- UL / cUL or ETL / cETL listed

### Abbreviation Key

#### Lamps

100W A21      Medium Base, 100W Max, Incandesent or LED

#### Finish Types

PC              Powder Coat

#### Diffuser Types

AD              Standard Acrylic Diffuser

PA              Premium Acrylic Diffuser

#### Options

FD              Frosted Diffuser