

## Spokane Series Pendant



Model Number	Lamping Code	Body Lamping	Up Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting
<b>SP2410L</b>  • W 24" • HT 10" • OAH 36" (OverAll Height)	EXI	4,700lm LED (31W)	2,700lm LED	2,000lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
	ELR	3-100W A21 (300W)			1	PC	WA PA	ST CH SM SP MS AS RS CS
<b>SP3013L</b>  • W 30" • HT 13" • OAH 48" (OverAll Height)	ELX	9,600lm LED (70W)	6,400lm LED	3,200lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
	ELY	15,300lm LED (109W)	10,200lm LED	5,100lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
<b>SP3615L</b>  • W 36" • HT 15" • OAH 60" (OverAll Height)	ELU	3-100W A21 (300W)			1	PC	WA PA	ST CH SM SP MS AS RS CS
	FJW	6-100W A21 (600W)			1	PC	WA PA	ST CH SM SP MS AS RS CS

	EME	9,600lm LED (70W)	6,400lm LED	3,200lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
	EMF	16,400lm LED (119W)	10,900lm LED	5,400lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
<b>SP4218L</b>	EML	14,400lm LED (93W)	10,800lm LED	3,600lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
<ul style="list-style-type: none"> <li>• W 42"</li> <li>• HT 18"</li> <li>• OAH 72" (OverAll Height)</li> </ul>								
	EMM	28,700lm LED (212W)	21,500lm LED	7,100lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
	EMG	6-100W A21 (600W)			1	PC	WA PA	ST CH SM SP MS AS RS CS
	EMH	12-100W A21 (1200W)			1	PC	WA PA	ST CH SM SP MS AS RS CS

**SAMPLE CATALOG NUMBER**

**Model Number - Lamping Code - Finish - Mounting - Diffuser - Options**

**PRODUCT FEATURES**

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

**Abbreviation Key**

**Lamps**

100W A21 Medium Base, 100W Max, Incandesent or LED

**Finish Types**

PC Powder Coat

**Diffuser Types**

WA Standard Acrylic Diffuser

PA Premium Acrylic Diffuser

**Mountings**

ST Stem  
 CH Chain  
 SM Surface Mount Chain  
 SP Steep Pitch Canopy for Stem  
 MS Multi-Stem  
 AS Air Craft Cable & Stem  
 RS Rod & Stem  
 CS Chain & Stem

0

D1