

Spokane Series Pendant



Model Number	Lamping Code	Body Lamping	Up Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting
SP2410L • W 24" • HT 10" • OAH 36" (OverAll Height)	EXI	4,700lm LED (31W)	2,700lm LED	2,000lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
	ELR	3-100W A21 (300W)			1	PC	WA PA	ST CH SM SP MS AS RS CS
SP3013L • W 30" • HT 13" • OAH 48" (OverAll Height)	ELX	9,600lm LED (70W)	6,400lm LED	3,200lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
	ELY	15,300lm LED (109W)	10,200lm LED	5,100lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
	ELU	3-100W A21 (300W)			1	PC	WA PA	ST CH SM SP MS AS RS CS
SP3615L • W 36" • HT 15" • OAH 60" (OverAll Height)	EME	9,600lm LED (70W)	6,400lm LED	3,200lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS

SP4218L • W 42" • HT 18" • OAH 72" (OverAll Height)	EMF	16,400lm LED (119W)	10,900lm LED	5,400lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
	FJW	6-100W A21 (600W)			1	PC	WA PA	ST CH SM SP MS AS RS CS
	EML	14,400lm LED (93W)	10,800lm LED	3,600lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
	EMM	28,700lm LED (212W)	21,500lm LED	7,100lm LED	1	PC	WA PA	ST CH SM SP MS AS RS CS
	EMG	6-100W A21 (600W)			1	PC	WA PA	ST CH SM SP MS AS RS CS
	EMH	12-100W A21 (1200W)			1	PC	WA PA	ST CH SM SP MS AS RS CS

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

PA Premium Acrylic Diffuser

Mountings

ST Stem

CH Chain

SM Surface Mount Chain

SP Steep Pitch Canopy for Stem

MS Multi-Stem

AS Air Craft Cable & Stem

RS Rod & Stem

CS Chain & Stem

Dimming Types

0	D1
1	D2