

## Spokane Series Wall Bracket



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Options
<b>SP1811B</b> • W 18 • HT 11	FBO	3,200lm LED (20W)	1	PC	AD PA	WM	D1 D2* FD
	FBM	1-100W A21 (100W)	1	PC	AD PA	WM	FD
<b>SP2413B</b> • W 24 • HT 13	FBR	3,200lm LED (20W)	1	PC	AD PA	WM	D1 FD
	FBP	1-100W A21 (100W)	1	PC	AD PA	WM	FD

### SAMPLE CATALOG NUMBER

**Model Number - Lamping Code - Finish - Mounting - Diffuser - Options**

### PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED or fluorescent lamping
- Wired for single circuit operation (Body Lamping)
- High power factor electronic ballast or LED driver
- Standard LED color temperature is 3000K with 80 CRI. Contact us for other color temperature or CRI options.
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Optional dimming ballast 120V or 277V (LED or fluorescent lamping)
- Mounts to standard electrical junction box (by others)
- LED Battery Back-Up Available
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

### Abbreviation Key

#### Lamps

100W A21      Medium Base, 100W Max, Incandesent or LED

#### Finish Types

PC      Powder Coat

#### Diffuser Types

AD      Standard Acrylic Diffuser

PA      Premium Acrylic Diffuser

#### Mountings

WM      Wall Mount

#### Dimming Types

0      D1

1      D2

#### Options

FD      Frosted Diffuser

