

Spokane Series Wall Bracket



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Options
SP1811B • W 18 • HT 11	FBO	3,200lm LED (20W)	1	PC	AD PA	WM	D1 D2* D4 D5 FD
	FBM	1-100W A21 (100W)	1	PC	AD PA	WM	FD
SP2413B • W 24 • HT 13	FBR	3,200lm LED (20W)	1	PC	AD PA	WM	D1 FD
	FBP	1-100W A21 (100W)	1	PC	AD PA	WM	FD

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED or fluorescent lamping
- Wired for single circuit operation (Body Lamping)
- High power factor electronic ballast or LED driver
- Standard LED color temperature is 3000K with 80 CRI. Contact us for other color temperature or CRI options.
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatability.
- Optional dimming ballast 120V or 277V (LED or fluorescent lamping)
- Mounts to standard electrical junction box (by others)
- LED Battery Back-Up Available
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

AD Standard Acrylic Diffuser

PA Premium Acrylic Diffuser

Mountings

WM Wall Mount

Dimming

D1 LED 0-10v dimming options include integral 120-277v dimming drivers

D2 LED Triac/ELV dimming options include integral 120v dimming drivers

D4 LED Triac dimming options include integral leading edge 120v dimming drivers

D5 LED ELV dimming options include integral trailing edge 120v dimming drivers

Options

FD Frosted Diffuser