

Savannah Series Pendant



Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
SV1024L • W 11 • HT 26 • OAH 72 (OverAll Height)	GBK	4-60W A19 (240W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
SV1226L • W 13 • HT 28 • OAH 96 (OverAll Height)	DVD	14,500lm LED (86W)	5,100lm LED (36W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	DNY	14,500lm LED (86W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	DNZ	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	DOA	23,100lm LED (146W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	ETG	23,100lm LED (146W)	10,400lm LED (76W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	DOB	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	FIY	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
SV1231L • W 13 • HT 33 • OAH 96 (OverAll Height)	DXL	14,500lm LED (86W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	DOS	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	DMF	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST	SQ	SIL

							CH SM SP		LOGO
	DKO	29,500lm LED (192W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	FIZ	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
SV1236L • W 12 • HT 38 • OAH 96 (OverAll Height)	GKG	10,800lm LED (60W)		1	PC	WA	ST CH SM SP	SQ	SIL LOGO
	GDZ	15,400lm LED (86W)	5,100lm LED (36W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	GEF	17,800lm LED (100W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	GES	24,900lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	GEV	39,000lm LED (267W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO
	GIX	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ	SIL LOGO

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 15'
DOOR HEIGHT: 7'
SILHOUETTE HEIGHT: 6'

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key	
Lamps	
60W A19	Medium Base, 60W Max, Incandesent or LED
100W PAR38	Medium Base, 100W Max, Incandesent or LED
Finish Types	
PC	Powder Coat
Diffuser Types	
WA	Standard Acrylic Diffuser
Mountings	
ST	Stem
CH	Chain
SM	Surface Mount Chain
SP	Steep Pitch Canopy for Stem
Louvers	
SQ	Square Cell
Dimming Types	
0	D1
1	D2
2	D3
Options	
SIL	Silhouette Symbol

