Savannah Series Wall Bracket






Model Number	Lamping Code	Body Lamping		Circuit	Finish	Diffuser	Mounting	Louver	Options
• W 8" • HT 16" • EXT 11"	AHZ	1-100	OW A21 (100W)	1	PC	WA	WM	SQ	SIL LOGO BL
SV1020B • W 10" • HT 20" • EXT 13"	DEM	3,900	DIm LED (24W)	1	PC	WA	WM	SQ	SIL LOGO BL
	AIB	1-100	OW A21 (100W)	1	PC	WA	WM	SQ	SIL LOGO BL
• W 12" • HT 24" • EXT 15"	FFX	5,400	Dim LED (33W)	1	PC	WA	WM	SQ	SIL LOGO BL
	GBW	2-100	OW A21 (200W)	1	PC	WA	WM	SQ	SIL LOGO BL

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

Mountings

WM Wall Mount

- Optional specialty diffuser materials available
 Energy efficient LED lamping
 High power factor electronic LED driver
 Wired for single circuit operation, Body Lamping
 Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability

 Standard LED CRI is 80 contact us for alternate CRI smaller life.
- Standard LED CRI is 80 contact us for alternate CRI availability
 Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
 Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Mounts to standard electrical junction box (by others)
 UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Louvers

SQ Square Cell

Dimming Types

0 D1 D3 2

Options

SIL Silhouette Symbol LOGO Custom Logo BL Bottom Lens