


# **Waycross Series Ceiling Mount**





Model Number	Lamping Code	Body Lamping	Circuit	Finish	Finish Accent		Mounting	Louver	Options
<b>WC1007C</b> • W 13 • HT 10	АНО	2-100W A21 (200W)	1	PC	WT CT	WA	CC	SQ	SIL LOGO
WC1208C  • W 16 • HT 12	GJJ	5,400lm LED (33W)	1	PC	WT CT	WA	CC	SQ	SIL LOGO
	AHQ	3-100W A21 (300W)	1	PC	WT	WA	СС	SQ	SIL

## SAMPLE CATALOG NUMBER

# Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



### PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- Stained Solid Red Oak Wood Trim
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available

  Francisco Figure 1 50 learning and a special spe
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability

#### Abbreviation Key

## Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

# Finish Types

PC Powder Coat

#### Finish Accent Types

WT Wood Trim
CT Custom Trim

### Diffuser Types

WA Standard Acrylic Diffuser

# Mountings

CC Ceiling Canopy

#### Louvers

SQ Square Cell

- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
  Standard LED dimming is 0-10v
  Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
  Mounts to standard electrical junction box (by others)
  UL / cUL or ETL / cETL listed
  Contact Us for more lamping options.

# **Dimming Types**

D1 1 D2

# Options

SIL Silhouette Symbol LOGO Custom Logo