
Winston Series Ceiling Mount





Model Number	Lamping Code	Body Lamping	Circuit	Finish	Finish Accent		Mounting	Louver	Options
WI1007C • W 12 • HT 10	АНО	2-100W A21 (200W)	1	PC	WT CT	WA	CC	SQ	SIL LOGO
WI1208C • W 14 • HT 12	GJJ	5,400lm LED (33W)	1	PC	WT CT	WA	CC	SQ	SIL LOGO
	AHQ	3-100W A21 (300W)	1	PC	WT CT	WA	СС	SQ	SIL

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- Stained Solid Red Oak Wood Trim
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Finish Accent Types

WT Wood Trim
CT Custom Trim

Diffuser Types

WA Standard Acrylic Diffuser

Mountings

CC Ceiling Canopy

Louvers

SQ Square Cell

- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
 Standard LED dimming is 0-10v
 Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
 Mounts to standard electrical junction box (by others)
 UL / cUL or ETL / cETL listed
 Contact Us for more lamping options.

Dimming Types

D1 1 D2

Options

SIL Silhouette Symbol LOGO Custom Logo