


Norwich Series Ceiling Mount



SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Hanging - Diffuser - Options

Model	Lamping Options										
Model Number	Lamping Code	Body Lamping	Voltage	Circuit	Finish	Louver	Hanging	Diffuser	Options	Dimensions	
NW1207C	AMZ	2-F32TBX (77W)	120/277	1	PC	CR	CC	AD	DM	W	12"
	AMY	2-MAX 100 IN/SBCF/LED (200W)	120	1		SQ		AG		HT	11"
								GA		OAH	N/A
NW1408C	ANB	2-F42TBX (99W)	120/277	1	PC	CR	CC	AD	DM	W	14"
	ANA	3-MAX 100 IN/SBCF/LED (300W)	120	1		SQ		AG		HT	13"
								GA		OAH	N/A
NW1609C	AND	3-F42TBX (148W)	120/277	1	PC	CR	CC	AD	DM	W	16"
	ANC	3-150A21 (450W)	120	1		SQ		AG		HT	14"
								GA		OAH	N/A
NW1811C	ANF	4-F42TBX (197W)	120/277	1	PC	CR	CC	AD	DM	W	18"
	ANE	3-150A21 (450W)	120	1		SQ		AG		HT	17"
								GA		OAH	N/A

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED or fluorescent lamping
- Wired for single circuit operation (Body Lamping)
- High power factor electronic ballast or LED driver
- Optional dimming ballast 120V or 277V (LED or fluorescent lamping)
- Mounts to standard 4" octagonal electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Dimensions

W	Width
HT	Height
OAH	Overall Height

Lamp Descriptions

150A21	150W A21, medium base
MAX 100 IN/SBCF/LED	Medium Base, 100W Max, Incandescent or LED
F32TBX	32W triple biax, 4-PIN GX24q-3 base
F42TBX	42W triple biax, 4-PIN GX24q-4 base

Finishes

PC	Powder Coat
----	-------------

Hanging Style

CC Ceiling Canopy

Diffusers

AD Acrylic (White Acrylic Standard)

AG Art Glass

GA Glass Alternative

Options

DM Dimming

Louver

CR CONCENTRIC RING (Not available on LED lighting)

SQ SQUARE CELL (Must be used on all LED lighting)