

Sacramento Series Ceiling Mount



SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Hanging - Diffuser - Options

Model	Lamping Options										
Model Number	Lamping Code	Body Lamping	Voltage	Circuit	Finish	Louver	Hanging	Diffuser	Options	Dimensions	
SC1806C	EDX	2,700lm LED (30W)	120/277	1	PC	SQ	CC	AD	DM	W	18"
	BCS	2-F26TBX (58W)	120/277	1	PB			FA	FD	HT	9"
	BCR	2-MAX 60 IN/SBCF/LED (120W)	120	1						OAH	N/A
SC2408C	EDY	2,700lm LED (30W)	120/277	1	PC	SQ	CC	AD	DM	W	24"
	EEH	6,300lm LED (50W)	120/277	1	PB			FA	FD	HT	11"
	BCU	2-F32TBX (77W)	120/277	1						OAH	N/A
	EDZ	2-F42TBX (99W)	120/277	1							
	BCT	3-MAX 60 IN/SBCF/LED (180W)	120	1							
SC3010C	BHS	2-F42TBX (99W)	120/277	1	PC	SQ	CC	AD	DM	W	30"
	CUH	4-F32TBX (154W)	120/277	1	PB			FA	FD	HT	12"
	BHR	3-MAX 100 IN/SBCF/LED (300W)	120	1						OAH	N/A
SC3612C	BHU	4-F42TBX (197W)	120/277	1	PC	SQ	CC	AD	DM	W	36"
	BHT	3-150A21 (450W)	120	1	PB			FA	FD	HT	13"
										OAH	N/A
SC4214C	BHW	6-F42TBX (296W)	120/277	1	PC	SQ	CC	AD	DM	W	42"
	DAS	8-F42TBX (394W)	120/277	1	PB			FA	FD	HT	15"
	BHV	6-MAX 100 IN/SBCF/LED (600W)	120	1						OAH	N/A

Scale



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED or fluorescent lamping
- Wired for single circuit operation (Body Lamping)
- High power factor electronic ballast or LED driver

Abbreviation Key

Dimensions

W	Width
HT	Height
OAH	Overall Height

Lamp Descriptions

150A21	150W A21, medium base
MAX 60 IN/SBCF/LED	Medium Base, 60W Max, Incandescent or LED
MAX 100 IN/SBCF/LED	Medium Base, 100W Max, Incandescent or LED
F26TBX	26W triple biax, 4-PIN GX24q-3 base

- Optional dimming ballast 120V or 277V (LED or fluorescent lamping)
- Mounts to standard 4" octagonal electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

F32TBX	32W triple biax, 4-PIN GX24q-3 base
F42TBX	42W triple biax, 4-PIN GX24q-4 base
LED	3000 Kelvin Warm White LED

Finishes

PC	Powder Coat
PB	Polished Brass

Hanging Style

CC	Ceiling Canopy
----	----------------

Diffusers

AD	Acrylic (White Acrylic Standard)
FA	Faux Alabaster

Options

DM	Dimming
DIM-010	0-10V four wire control dimming
FD	Frosted Diffuser

Louver

SQ	SQUARE CELL (Must be used on all LED lamping)
----	---